60W UI48/26 AUI4826 SERIES

FEATURES

Frequency 50/60Hz
Potted under vacuum
Split-bobbin
Temperature class ta 40°C/B
Weight: 0.53kg
Packaging unit: 10 pieces (tray)
Fixing material for 2.5mm (0.098 inch)
Self-tapping screws: DIN 7513 (M 3x8)
Sheet-metal screws: DIN 7971 (2.9x6.5)

OPTIONS

Bulk packaging is standard
Custom design available

COMMON APPLICATIONS

Medical equipments
Industrial equipments
Industrial controls
Test equipments
Industrial computers
Avionics & telecom

PHYSICAL CHARACTERISTICS



ELECTRICAL CHARACTERISTICS AT 25°C

Part Number	Primary (V)	Secondary (V/mA)	No-load voltage(V)	Fig.
AUI 482673	2*6	2*5000	2*6.6	1
AUI 482674	2*9	2*3333	2*9.9	1
AUI 482675	2*12	2*2500	2*13.1	1
AUI 482676	2*15	2*2000	2*16.4	1
AUI 482677	2*18	2*1667	2*19.7	1
AUI 482678	2*24	2*1250	2*26.3	1

TECHNICAL INFORMATION



ALL DIMENSIONS IN MM