

CK-4W Series

4W 4:1 Regulated Single & Dual output



Features

- Wide 4:1 Input Range
- 1500VDC Isolation, Up to 3500VDC
- Continuous Short Circuit Protection
- Efficiency up to 86%
- Operating Temperature Range -40 ~ 95°C max.



PART NUMBER STRUCTURE

CK - **24** **05** **S** **4** **H**
(1) (2) (3) (4) (5) (6)

(1) Series

(2) Input Voltage Range

24 - 9-36 V
48 - 18-72 V

(4) Output Type

S - Single Output
D - Dual Output

(3) Output Voltage

3R3 - 3.3 V
05 - 5.0 V
7R2 - 7.2 V
09 - 9.0 V
12 - 12 V
15 - 15 V
18 - 18 V
24 - 24 V

(5) Watt

(6) Isolation Voltage

Blank - 1500 VDC
H - 3500 VDC

CK-4W Series

4W 4:1 Regulated Single & Dual output



ALL SPECIFICATIONS ARE TYPICAL AT 25°C, NOMINAL INPUT AND FULL LOAD UNLESS OTHERWISE NOTED

Model Number	Input Voltage Range (VDC)	Input Current		Output Voltage (VDC)	Output Current		Efficiency @FL (% , typ.)	Capacitive Load @FL (µF, max.)
		No-Load (mA, max.)	Full Load (mA, typ.)		Min. load (mA)	Full load (mA)		
CK-243R3S4	9-36	12	215	3.3	0	1200	77	1000
CK-2405S4	9-36	15	206	5	0	800	81	1000
CK-247R2S4	9-36	15	199	7.2	0	555	84	680
CK-2409S4	9-36	15	197	9	0	444	85	220
CK-2412S4	9-36	15	199	12	0	333	84	100
CK-2415S4	9-36	15	199	15	0	266	84	220
CK-2418S4	9-36	15	199	18	0	222	84	10
CK-2424S4	9-36	18	201	24	0	166	83	100
CK-243R3D4	9-36	12	217	±3.3	0	±606	77	±470
CK-2405D4	9-36	15	206	±5	0	±400	81	±100
CK-247R2D4	9-36	15	201	±7.2	0	±277	83	±220
CK-2409D4	9-36	18	209	±9	0	±222	80	±47
CK-2412D4	9-36	15	199	±12	0	±166	84	±47
CK-2415D4	9-36	20	204	±15	0	±133	82	±10
CK-2418D4	9-36	25	201	±18	0	±111	83	±100
CK-2424D4	9-36	25	209	±24	0	±83	80	±22
CK-483R3S4	18-72	10	108	3.3	0	1200	77	1000
CK-4805S4	18-72	8	102	5	0	800	82	220
CK-487R2S4	18-72	10	102	7.2	0	555	82	470
CK-4809S4	18-72	10	99	9	0	444	85	330
CK-4812S4	18-72	12	101	12	0	333	83	1000
CK-4815S4	18-72	10	99	15	0	266	85	47
CK-4818S4	18-72	10	97	18	0	222	86	10
CK-4824S4	18-72	15	100	24	0	166	84	33
CK-483R3D4	18-72	10	105	±3.3	0	±606	80	±680
CK-4805D4	18-72	8	103	±5	0	±400	81	±330
CK-487R2D4	18-72	15	106	±7.2	0	±277	79	±47
CK-4809D4	18-72	15	105	±9	0	±222	80	±47
CK-4812D4	18-72	12	100	±12	0	±166	84	±100
CK-4815D4	18-72	15	101	±15	0	±133	83	±100
CK-4818D4	18-72	15	105	±18	0	±111	80	±22
CK-4824D4	18-72	15	102	±24	0	±83	82	±10

CK-4W Series

4W 4:1 Regulated Single & Dual output



INPUT SPECIFICATIONS					
Parameter	Conditions	Min.	Typ.	Max.	Unit
Input Voltage Range	24V Input	9	24	36	VDC
	48V Input	18	48	72	
Input Filter		Pi Type			
Input Reflected Ripple Current (1)			35		mApk-pk
Start up Time	Nominal Vin and constant resistive load		500		ms
Recommended input fuse (slow blow)	24V Input	0.8			A
	48V Input	0.4			
Note :					
1. Measured with a simulated source inductance of 12μH and a source capacitor Cin (47μF, ESR<1.0Ω at 100kHz).					

OUTPUT SPECIFICATIONS						
Parameter	Conditions		Min.	Typ.	Max.	Unit
Output Voltage Accuracy	3.3V Output		-2.0		+2.0	%
	Other Output		-1.0		+1.0	
Line Regulation			-0.5		+0.5	%
Load Regulation	From 0% to 100% Load	3.3V Output	-1.5		+1.5	%
		Other Output	-0.5		+0.5	
Cross Regulation	Asymmetrical Load 25% / 100% for Dual Output		-5		+5	%
Ripple & Noise (1)	20MHz bandwidth	24V Output			150	mVpk-pk
		Other Output			60	
Short Circuit Protection			Indefinite (Automatic Recovery)			
Temperature Coefficient			-0.02		+0.02	%/°C
Maximum Capacitive Load	Nominal Vin and constant resistive load		See Table			
Note :						
1. Measured with a 1.0μF MLCC.						

ABSOLUTE MAXIMUM RATINGS					
Parameter	Conditions	Min.	Typ.	Max.	Unit
Input Surge Voltage (100 ms)	24V Input			40	VDC
	48V Input			80	
Soldering Temperature	1.5mm from case 10sec max.			260	$^{\circ}$ C
Note : These are stress ratings. Exposure of devices to any of these conditions may adversely affect long-term reliability.					

GENERAL SPECIFICATIONS					
Parameter	Conditions	Min.	Typ.	Max.	Unit
Isolation Voltage	Input-output, and rated for 60sec	Standard Type	1500		VDC
		Suffix "H"	3500		
	Case-I/O, and rated for 60sec	1000			
Isolation Resistance	Input-output	1000			M Ω
Isolation Capacitance	Input-output		500		pF
Switching Frequency			266		kHz
MTBF	MIL-HDBK-217 F @ 25 $^{\circ}$ C	1121			k hours
Safety Approval	IEC / EN / UL 62368-1	Designed to meet			
Environmental compliance		RoHS			

CK-4W Series

4W 4:1 Regulated Single & Dual output



ENVIRONMENT SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Operating Ambient Temperature	See the Derating Curve	-40		85	°C
Maximum Case Temperature				100	°C
Thermal Impedance		25			°C/W
Storage Humidity				95	% rel. H
Storage Temperature		-55		125	°C
Cooling	Natural Convection	30-65 LFM			

EMC SPECIFICATIONS

Parameter	Standard	Condition	Criterion
Conducted Emissions	EN55032	with external components	A
Radiated Emissions	EN55032		A
ESD	IEC 61000-4-2	Air: ±8kV / Indirect: ±6kV	A
RS	IEC 61000-4-3	10V/m	A
EFT	IEC 61000-4-4	±2kV	A
Surge	IEC 61000-4-5	±1kV with external components	A
CS	IEC 61000-4-6	10Vrms	A
PFMF	IEC 61000-4-8	1A/m	A

PHYSICAL SPECIFICATIONS


Parameter	Value
Case Material	Copper
Pin Material	Ø0.5mm Brass Solder-coated
Potting Material	Epoxy (UL94V-0 rated)
Weight	17.0 g, typ.
Dimensions	1.25" x 0.8" x 0.4"

CK-4W Series


4W 4:1 Regulated Single & Dual output




ELECTRICAL CHARACTERISTIC CURVES



Efficiency 77% ~ 80% Models



Efficiency 81% ~ 83% Models




Efficiency 84% ~ 86% Models

TEST CONFIGURATIONS

Input Reflected Ripple Current Test Step

Input reflected ripple current is measured with a source inductor L_{in} (12 μ H) and a source capacitor C_{in} (47 μ F, ESR<1.0 Ω at 100kHz) at nominal input and full load.




CK-4W Series

4W 4:1 Regulated Single & Dual output

DESIGN & FEATURE CONFIGURATIONS



EMC Filter

The part (1) Circuit is used to meet Surge & EFT test, and the part (2) Circuit is used to meet EMI test.



	C1	C2	L	C3
CK-24XXX4	NIPPON Chemi-con KY series 220μF, 100V	Nichicon PW series 68μF, 100V	12μH	Nichicon PW series 33μF, 100V
CK-48XXX4				

MECHANICAL SPECIFICATIONS



Notes : All dimensions are typical in millimeters (inches).

1. Pin diameter: 0.5 ± 0.05 (0.02 ± 0.002)
2. Pin pitch and length tolerance: ± 0.35 (± 0.014)
3. Case Tolerance: ± 0.5 (± 0.02)
4. Stand-off tolerance: ± 0.1 (± 0.004)


PIN CONNECTIONS

PIN NUMBER	SINGLE	DUAL
2	-Vin	-Vin
3	-Vin	-Vin
9	N.P.	COM
11	N.C.	-Vout
14	+Vout	+Vout
16	-Vout	COM
22	+Vin	+Vin
23	+Vin	+Vin

*N.P. : No PIN

*N.C. : No Connection

RECOMMENDED FOOTPRINT DETAILS



Notes : 1. All dimensions are typical in millimeters (inches).

Through hole (black) 2 ~ 23: $\varnothing 0.80$ (0.031)

Top view pad (green) 2 ~ 23: $\varnothing 1.00$ (0.039)

Bottom view pad (pink) 2 ~ 23: $\varnothing 1.60$ (0.063)